

COLORADO OTR Tire Catalogue



k2global
OTR Tires



COLORADO E4 Pattern Tires

Earthmover

Size	TRA	PR	TreadDepth(32 nd)	Standard Rim	Weight(kgs)	Max Load (kg) / Pressure (kpa)		Inflated Dimensions (mm)	
						@10km/h	@50km/h	Section Width	Overall Diameter
59/80-63	E4	88	120	44.00/5.0	5000		111000/700	1469	4026
55/80-63	E4	86	111	41.00/5.0	4682		103000/700	1379	3912
53/80-63	E4	78	111	36.00/5.0	4318		92500/700	1300	3780
40.00-57	E4	78	104	29.00/6.0	3417	10000/825	60000/700	1098	3594
40.00-57	E4	68	104	29.00/6.0	3384	92500/725	54500/550	1098	3582
37.00-57	E4	68	104	27.00/6.0	3000	80500/725	51500/530	1017	3439
36.00-51	E4	58	111	26.00/5.0	2655	71000/675	41460/530	1016	3230
36.00-51	E4	58	104	26.00/5.0	2473	71000/675	41250/525	999	3233
33.00-51	E4	58	96	24.00/5.0	2005	61500/750	35500/575	904	3053
30.00-51	E4	52	88	22.00/4.5	1773	53000/750	30000/550	820	2908
27.00-49	E4	48	82	19.50/4.0	1186	43700/775	25000/575	787	2680
27.00-49	E4	48	79	19.50/4.0	1233	43700/755	25000/575	735	2703
24.00-49	E4	48	73	17.00/3.5	1012	37500/850	21800/650	650	2531
33.25-29	E4	46	80	27.00/3.5	818	29000/650	18500/525	845	2090
24.00-35	E4	48	72	17.00/3.5	862	31500/850	18500/650	650	2130
21.00-35	E4	36	57	15.00/3.0	605	23000/750	12800/550	575	2005
18.00-33	E4	42	68	13.00/2.5	451	20500/975		495	1823
18.00-25	E4	40	67	13.00/2.5	432		9750/700	495	1671



COLORADO Radial OTR Tires

Earthmover

Size	TRA	Star Rating	TreadDepth(32 nd)	Standard Rim	Max Load (kg) / Pressure (kpa)		Inflated Dimensions (mm)	
					@10km/h	@50km/h	Section Width	Overall Diameter
59/80R63	E4	**	120	44.00/5.0	104000/680	99000/600	1503	4028
55/80R63	E4	**	111	41.00/5.0	99840/700	93000/600	1400	3887
53/80R63	E4	**	111	36.00/5.0	88030/700	82000/600	1342	3766
40.00R57	E4	**	104	29.00/6.0	66150/750	60000/600	1218	3766
37.00R57	E4	**	104	27.00/6.0	58450/750	53000/600	1040	3456
36.00R51	E4	**	104	26.00/5.0	51000/750	46250/600	1097	3338
33.00R51	E4	**	96	24.00/5.0	41400/700	38750/600	992	3202
27.00R49	E4	**	82	19.50/4.0	29850/800	27250/650	818	2819
24.00R35	E4	**	72	17.00/3.5	25250/380	23850/340	659	2156
18.00R33	E4	**	68	13.00/2.5	18500/825	10900/700	498	1877
29.5R25	L3/E3	**	59	25.00/3.5		14016/525	749	1874
26.5R25	L3/E3	**	47	22.00/3.0	18500/650	11500/525	673	1798
23.5R25	L3/E3	**	53	19.50/2.5	14500/650	9250/525	597	1673
23.5R25	L3/E3	**	43	19.50/2.5	14500/650	9250/525	597	1673
20.5R25	L3/E3	**	39	14.00/2.0	11500/650	7300/525	521	1548
17.5R25	L3/E3	**	35	14.00/1.5	8500/650	5450/525	445	1399



COLORADO E4 Pattern Tires

Earthmover

Size	TRA	PR	TreadDepth(32 nd)	Standard Rim	Weight(kgs)	Max Load (kg) / Pressure (kpa)		Inflated Dimensions (mm)	
						@10km/h	@50km/h	Section Width	Overall Diameter
59/80-63	E4	88	120	44.00/5.0	5000		111000/700	1469	4026
55/80-63	E4	86	111	41.00/5.0	4682		103000/700	1379	3912
53/80-63	E4	78	111	36.00/5.0	4318		92500/700	1300	3780
40.00-57	E4	78	104	29.00/6.0	3417	10000/825	60000/700	1098	3594
40.00-57	E4	68	104	29.00/6.0	3384	92500/725	54500/550	1098	3582
37.00-57	E4	68	104	27.00/6.0	3000	80500/725	51500/530	1017	3439
36.00-51	E4	58	111	26.00/5.0	2655	71000/675	41460/530	1016	3230
36.00-51	E4	58	104	26.00/5.0	2473	71000/675	41250/525	999	3233
33.00-51	E4	58	96	24.00/5.0	2005	61500/750	35500/575	904	3053
30.00-51	E4	52	88	22.00/4.5	1773	53000/750	30000/550	820	2908
27.00-49	E4	48	82	19.50/4.0	1186	43700/775	25000/575	787	2680
27.00-49	E4	48	79	19.50/4.0	1233	43700/755	25000/575	735	2703
24.00-49	E4	48	73	17.00/3.5	1012	37500/850	21800/650	650	2531
33.25-29	E4	46	80	27.00/3.5	818	29000/650	18500/525	845	2090
24.00-35	E4	48	72	17.00/3.5	862	31500/850	18500/650	650	2130
21.00-35	E4	36	57	15.00/3.0	605	23000/750	12800/550	575	2005
18.00-33	E4	42	68	13.00/2.5	451	20500/975		495	1823
18.00-25	E4	40	67	13.00/2.5	432		9750/700	495	1671



COLORADO Radial OTR Tires

Earthmover

Size	TRA	Star Rating	TreadDepth(32 nd)	Standard Rim	Max Load (kg) / Pressure (kpa)		Inflated Dimensions (mm)	
					@10km/h	@50km/h	Section Width	Overall Diameter
59/80R63	E4	**	120	44.00/5.0	104000/680	99000/600	1503	4028
55/80R63	E4	**	111	41.00/5.0	99840/700	93000/600	1400	3887
53/80R63	E4	**	111	36.00/5.0	88030/700	82000/600	1342	3766
40.00R57	E4	**	104	29.00/6.0	66150/750	60000/600	1218	3766
37.00R57	E4	**	104	27.00/6.0	58450/750	53000/600	1040	3456
36.00R51	E4	**	104	26.00/5.0	51000/750	46250/600	1097	3338
33.00R51	E4	**	96	24.00/5.0	41400/700	38750/600	992	3202
27.00R49	E4	**	82	19.50/4.0	29850/800	27250/650	818	2819
24.00R35	E4	**	72	17.00/3.5	25250/380	23850/340	659	2156
18.00R33	E4	**	68	13.00/2.5	18500/825	10900/700	498	1877
29.5R25	L3/E3	**	59	25.00/3.5		14016/525	749	1874
26.5R25	L3/E3	**	47	22.00/3.0	18500/650	11500/525	673	1798
23.5R25	L3/E3	**	53	19.50/2.5	14500/650	9250/525	597	1673
23.5R25	L3/E3	**	43	19.50/2.5	14500/650	9250/525	597	1673
20.5R25	L3/E3	**	39	14.00/2.0	11500/650	7300/525	521	1548
17.5R25	L3/E3	**	35	14.00/1.5	8500/650	5450/525	445	1399

k2global
OTR Tires



K2 Global LLC
1100 Quaker Hill Drive, Suite 322
Alexandria, Virginia 22314
USA
(802) 734- 8678

usa@k2-global.com
www.k2-global.com